

TEF-GEL

PENETRATING GEL LUBRICANT with TEFLON®

- **High Tack**
- **Resists Water Washout**
- **Provides a Moisture Resistant Film**
- **Protects Against Rust and Corrosion**
- **Effective at Temperatures From -30°F to +500°F**
- **Penetrates as an Oil then Sets up to a Tacky Grease-Like Gel**



A high tack lubricating gel which provides superior lubrication from -30°F to +500°F. Penetrates as an oil to lubrication point then forms into a tacky, grease-like gel. Contains Teflon® for added friction reduction. Provides superior stringing action. Resists water washout and weathering. Residual film prevents rust and corrosion. Safe on most plastics and paints.

• **RESISTS WATER WASHOUT**


Teflon® - A registered Trademark of E.I. DuPont de Nemours & Co., Inc.

FOR USE ON:

- **Chains • Gears • Hinges • Sprockets**
- **Cable • Wire Rope • Slides • Valves**
- **Bushings • Pistons • Shafts • Rings**

FOR USE BY:

- **Machine Shops**
- **Light and Heavy Manufacturing**
- **HVAC, Plumbing and Other Trades**
- **Automotive**
- **All Repair Operations**



SOUTHWEST

SPECIALTY

Odessa, TX 79762 • PH: (432) 363-3797